

MTH800 Double Tom Holder

INSTRUCTION MANUAL

■ Please read through this instruction manual before start to use.

Thank you for your purchase of the MTH800 double tom holder. To ensure the safe and efficient use of this product, please read through this manual before use. Store this manual in a convenient place for future reference.

Product Details

MTH800 double tom holder can be used on a bass drum with a 25.4mm mounting bracket.

Assembly method

1. Loosen the T-bolt (G) on the mounted bass drum bracket, insert the tom holder (MTH800) and then tighten the T-bolt firmly to secure it. Loosen the bolt located on the Memory Lock (F) here. Adjust the toms so that it does not make contact with the top of the bass drum shell to prevent damage to the bass drum shell.
 2. Slide the memory lock attached to the tom tom (*Please note memory lock are not included on all series) onto ball rods (A) and (B). Then, slide the tom tom brackets onto ball rods A and B. After finding the desired position, secure the memory lock with a drum key.
 3. Loosen T-nut (C) to adjust the left tom tom, and loosen T-nut (D) to adjust the right tom tom to the desired position. It is also possible to loosen the square head bolt (E) and slide the right unit on the tom holder to fine-tune space between the two tom toms.
 4. When changing the height of both tom toms, raise or lower the tom holder's height. Be sure to support the tom tom with one hand firmly, and slowly loosen the T bolt (G) with the other hand when adjusting. When you find the desired position, set it so that the tab of Memory Lock (F) is flush with the tom holder base's groove and tighten the square head bolt with the drum key.
- *If you do not support the tom while adjusting the height, it may suddenly drop, resulting in injury or damage to the top surface of the bass drum shell.
5. By removing the square head bolt (E), the entire unit housing the ball rod (A) can be removed, and it can also be used as a single tom holder.
- ※ Due to excessive use, when the toms' position has changed from its original position even when properly securing the T-nut, you can use commercially bought grease to restore proper support. Remove the tom from the rod, loosen the T-nut, and then apply a small amount of grease to the bolt.

